



ALIZE 3000

PORTABLE POWER

50Hz range Prestige

PRODUCT ADVANTAGES

- Large Autonomy
- Soundproofing and against shocks panels
- Complete connection interface deported
- HONDA Professional Engine
- Solid and high-performance equipment

Zoom

Top of the range equipment that is efficient and with low noise emissions, for a wide range of standard requirements.

Divers

Top of the range equipment that is efficient and with low noise emissions, for a wide range of standard requirements.



This product is QUALIGEN certified. Defined by the SIMOTHERM and GIGREL professional organisations, the QUALIGEN charter is intended to provide a label for equipment compliant with current regulations (user safety, noise level, power, sales information, After Sales Service) in order to provide the highest level of quality of our and thus to guarantee the users safety.

ALIZE 3000

GENERAL SPECIFICATIONS

Range	Prestige
Frequency (Hz)	50
Max. power (LTP) (kW)	2.80
Max power. (LTP) (kVA)	3.50
Nominal voltage (V)	230
Number of phase	Single phase - 230V
Guaranteed acoustic power Lw(A)	94
Noise level dB(A) - 1m	80
Noise level dB(A) - 7m	65

ENGINE SPECIFICATIONS

Engine trademark	Honda
Engine type	GX 200
Distribution	O.H.V.
Start	Launcher
Fuel	Petrol (unlead)
Autonomy (h)	9.20
Consumption (L/h]	1.30
Tank (L)	12
Oil Guard	Yes
Capacity (cm3)	196
Oil capacity (L)	0.60

ALTERNATOR SPECIFICATIONS

Type	Without collar or brush
Regulation	Mechanical
Protection class	IP 23
Insulation class	H

PLUGS AND PANEL DESCRIPTIVE

2 230V 10/16A sockets - circuit breaker

DIMENSIONS AND WEIGHT

Length (cm)	57
Width (cm)	45
Height (cm)	46
Dry Weight (kgs)	46

PACKAGING

Packaging type	Box
Length (cm)	58
Width (cm)	47
Height (cm)	47
Pallet type	140/110
Number of box by pallet	15
Pallet height (cm)	154

ALIZE 3000 - PORTABLE POWER - 50Hz range Prestige

This document is not contractual - The SDMO company reserves the right to modify any of the characteristics stated in this document without notice, in a constant effort to improve the quality of its products.

SDMO Industries - 12bis, rue de la Villeneuve - CS 92848 - 29228 BREST CEDEX 2 - France - Tel +33(0)2 98 41 41 41 - Fax +33 (0)2 98 41 63 07 - www.sdmo.com

OPTIONS



R05M	Manual changeover switch	The manual changeover switch is used to connect and disconnect a generating set manually to a domestic circuit when there is a power cut.
R06	Trolley kit R06	Trolley kit for 2 and 3 kW generating sets.
RBH1	Cans of oil RBH1	Box of 24 0.5L cans of oil or 20 1 L cans of oil (SAE 15W40)
RBH0-5	Cans of oil RBH0-5	Box of 24 0.5L cans of oil or 20 1 L cans of oil (SAE 15W40).
RHO	Protection cover RHO	Cover for SDMO generator sets and petrol or diesel driven pumps
RPM	Set of male plugs RPM	Male plugs for all models made up of : 2 x 16 A/230 V, EEC17: 1 x 16A/230 V, 1 x 32A/230 V and 1 x 16A/400V
RPQ	Earth spike RPQ	For earthing your generator set. Galvanised 1 m long spike, supplied with 2 m of 10 mm ² cable.