



## ALIZE 7500 TE

PORTABLE POWER

50Hz range Prestige

### PRODUCT ADVANTAGES

- Very large Autonomy
- Electric starter with batteries without maintenance
- HONDA Professional Engine
- Very Silent
- Easy movement thanks to the standard wheels

### Zoom

Top of the range equipment that is efficient and with low noise emissions, for a wide range of standard requirements.

### Divers

Top of the range equipment that is efficient and with low noise emissions, for a wide range of standard requirements.



This product is QUALIGEN certified. Defined by the SIMOTHERM and GIGREL professional organisations, the QUALIGEN charter is intended to provide a label for equipment compliant with current regulations (user safety, noise level, power, sales information, After Sales Service) in order to provide the highest level of quality of our and thus to guarantee the users safety.

## ALIZE 7500 TE

### GENERAL SPECIFICATIONS

Range	Prestige
Frequency (Hz)	50
Max. power (LTP) (kW)	5.60
Max power. (LTP) (kVA)	6.60
Nominal voltage (V)	400
Number of phase	Three phase - 400 V
Guaranteed acoustic power Lw(A)	94
Noise level dB(A) - 1m	79
Noise level dB(A) - 7m	65

### ENGINE SPECIFICATIONS

Engine trademark	Honda
Engine type	GX 390
Distribution	O.H.V.
Start	Electrical
Fuel	Petrol (unlead)
Autonomy (h)	9.60
Consumption (L/h]	2.50
Tank (L)	24
Oil Guard	Yes
Capacity (cm3)	389
Oil capacity (L)	1.10

### ALTERNATOR SPECIFICATIONS

Type	With collar and brush
Regulation	Mechanical
Protection class	IP 23
Insulation class	H

### PLUGS AND PANEL DESCRIPTIVE

2 230V 10/16A sockets - circuit breaker + 1 400V 16A socket - circuit breaker + hour meter

### DIMENSIONS AND WEIGHT

Lenght (cm)	78
Width (cm)	59
Height (cm)	75.50
Dry Weight (kgs)	132

### PACKAGING

Packaging type	Box / Pallet
Length (cm)	80
Width (cm)	61
Height (cm)	89.50
Number of box by pallet	0
Pallet height (cm)	0

## ACCESSORIES SUPPLIED



Funnel

User and maintenance manual

## OPTIONS



R03B	Differential box R03B	This set includes a differential switch, a hour meter, the plugs and a thermal circuit breaker.
R05A	Automatic mains failure panel R05A	Automatic start, remote control, start on dry contact.
RBH1	Cans of oil RBH1	Box of 24 o.5L cans of oil or 20 1 L cans of oil (SAE 15W40)
RBH0-5	Cans of oil RBH0-5	Box of 24 0.5L cans of oil or 20 1 L cans of oil (SAE 15W40).
RPM	Set of male plugs RPM	Male plugs for all models made up of : 2 x 16 A/230 V, EEC17: 1 x 16A/230 V, 1 x 32A/230 V and 1 x 16A/400V
RPQ	Earth spike RPQ	For earthing your generator set. Galvanised 1 m long spike, supplied with 2 m of 10 mm <sup>2</sup> cable.