



DX 6000 TE XL C

PORTABLE POWER

50Hz range Diesel

PRODUCT ADVANTAGES

- YANMAR Professional Engine
- Electric starter with batteries without maintenance
- Large Autonomy
- Low consumption
- Solid and high-performance equipment

Zoom

A both large autonomy and very long life for professional applications.

Divers

A both large autonomy and very long life for professional applications.



DX 6000 TE XL C

GENERAL SPECIFICATIONS

Range	Diesel
Frequency (Hz)	50
Max. power (LTP) (kW)	5.20
Max power. (LTP) (kVA)	6.50
Nominal voltage (V)	400
Number of phase	Three phase - 400 V
Guaranteed acoustic power Lw(A)	106
Noise level dB(A) - 1m	92
Noise level dB(A) - 7m	78

ENGINE SPECIFICATIONS

Engine trademark	Yanmar
Engine type	L100
Distribution	Fuel O.H.V.
Start	Electrical
Fuel	Fuel
Autonomy (h)	9.20
Consumption (L/h]	1.30
Tank (L)	12
Oil Guard	Yes
Capacity (cm3)	406
Oil capacity (L)	1.65

ALTERNATOR SPECIFICATIONS

Type	With collar and brush
Regulation	Mechanical
Protection class	IP 23
Insulation class	H

PLUGS AND PANEL DESCRIPTIVE

1 230V 10/16A socket - circuit breaker + 1 400V 16A socket - circuit breaker

DIMENSIONS AND WEIGHT

Length (cm)	87
Width (cm)	57
Height (cm)	55.50
Dry Weight (kgs)	106

PACKAGING

Packaging type	Box / Pallet
Length (cm)	88
Width (cm)	58.50
Height (cm)	70
Number of box by pallet	0
Pallet height (cm)	0

DX 6000 TE XL C - PORTABLE POWER - 50Hz range Diesel

This document is not contractual - The SDMO company reserves the right to modify any of the characteristics stated in this document without notice, in a constant effort to improve the quality of its products.

SDMO Industries - 12bis, rue de la Villeneuve - CS 92848 - 29228 BREST CEDEX 2 - France - Tel +33(0)2 98 41 41 41 - Fax +33 (0)2 98 41 63 07 - www.sdmo.com

OPTIONS



R03	Differential box R03	This set includes a differential switch and a thermal circuit breaker.
R05A	Automatic mains failure panel R05A	Automatic start, remote control, start on dry contact.
R05A	Automatic mains failure panel R05A	Automatic start, remote control, start on dry contact.
R07	Trolley kit R07	Trolley kit for generating sets > 3 kW with a stretcher system for easy handling.
RBH1	Cans of oil RBH1	Box of 24 0.5L cans of oil or 20 1 L cans of oil (SAE 15W40)
RBH0-5	Cans of oil RBH0-5	Box of 24 0.5L cans of oil or 20 1 L cans of oil (SAE 15W40).
RH2	Cover RH2	Cover for SDMO generator sets and petrol or diesel driven pumps
RPM	Set of male plugs RPM	Male plugs for all models made up of : 2 x 16 A/230 V, EEC17: 1 x 16A/230 V, 1 x 32A/230 V and 1 x 16A/400V
RPQ	Earth spike RPQ	For earthing your generator set. Galvanised 1 m long spike, supplied with 2 m of 10 mm ² cable.