



HP 2.26 H

PORTABLE POWER

Water Pumps Range SPECIALIST AQUALINE

PRODUCT ADVANTAGES

- HONDA Professional Engine
- Automatic priming
- Solid and high-performance equipment
- Offeres accessories
- High-pressure equipment

With nearly 6 bar of pressure, the HP 2.26 H can be used for high-pressure cleaning of machinery, such as agricultural vehicles. When combined with the nozzle kit, it can be used to suppress fires.

Range SPECIALIST AQUALINE

High performance under extreme conditions.



HP 2.26 H

WATER PUMP SPECIFICATIONS

Range	SPECIALIST AQUALINE
Type liquid	High voltage use
Suction diameter [mm]	50
Backflow diameter (mm)	50
Outflow maximum (L/min)	440
Outflow maximum (m3/h)	26.40
Lifting height (m)	57
Suction height (m)	8
Granulometry (mm)	8
Automatic priming	Yes
Fuel	Petrol
Tank (L)	3.10
75% cons. (l/h) *	0.90
75% Autonomy (h) *	3.40
Sound power level guaranteed LwA dB(A)	108
Acoustic pressure level @1m in dB(A)	92
Acoustic pressure level @7m in dB(A)	77

ENGINE SPECIFICATIONS

Engine brand	HONDA
Engine ref.	GX160
Distribution	O.H.V.
Start	Starter
Low Oil pressure shutdown	Oui
Displacement (cm3)	163
Oil capacity (L)	0.60

DIMENSIONS AND WEIGHT

Lenght (cm)	41.50
Width (cm)	54.50
Height (cm)	45.50
Dry Weight (kg)	30

PACKAGING

Packaging type	Box
Length (cm)	54
Width (cm)	42
Height (cm)	45
Weight (kg)	35
Pallet type	120/80
Number of box by pallet	12
Pallet height (cm)	148
weight of the packaged Pallet (kg)	430



ACCESSORIES SUPPLIED



Inlet filter
Screw-on connectors



Circlips
User and maintenance manual

OPTIONS



RBH1	RBH1	Box of 24 0.5L cans of oil or 20 1 L cans of oil (SAE 15W40)
RBH0-5	RBH0-5	Box of 24 0.5L cans of oil or 20 1 L cans of oil (SAE 15W40).
RHO	RHO	Cover for SDMO 's generating sets, welding sets and water pumps