



HX 5000 T S

PORTABLE POWER

50Hz range Intens

PRODUCT ADVANTAGES

- HONDA Professional Engine
- Compact frame with protection panels against shocks
- Solid and high-performance equipment

Zoom

robustness, endurance and simple to use equipments for repetitive operations and in difficult conditions.

Divers

robustness, endurance and simple to use equipments for repetitive operations and in difficult conditions.



HX 5000 T S

GENERAL SPECIFICATIONS

Range	Intens
Frequency (Hz)	50
Max. power (LTP) (kW)	4
Max power. (LTP) (kVA)	5
Nominal voltage (V)	400
Number of phase	Three phase - 400 V
Guaranteed acoustic power Lw(A)	102
Noise level dB(A) - 1m	84
Noise level dB(A) - 7m	70

ENGINE SPECIFICATIONS

Engine trademark	Honda
Engine type	GX 270
Distribution	O.H.V.
Start	Launcher
Fuel	Petrol (unlead)
Autonomy (h)	2.50
Consumption (L/h]	2.10
Tank (L)	5.30
Oil Guard	Yes
Capacity (cm3)	270
Oil capacity (L)	1.10

ALTERNATOR SPECIFICATIONS

Type	With collar and brush
Regulation	Mechanical
Protection class	IP 23
Insulation class	H

PLUGS AND PANEL DESCRIPTIVE

1 230V 10/16A socket - circuit breaker + 1 400V 16A socket - circuit breaker

DIMENSIONS AND WEIGHT

Lenght (cm)	71.50
Width (cm)	57
Height (cm)	49
Dry Weight (kgs)	68

PACKAGING

Packaging type	Box
Length (cm)	73
Width (cm)	58
Height (cm)	49.50
Pallet type	120/80
Number of box by pallet	6
Pallet height (cm)	162

HX 5000 T S - PORTABLE POWER - 50Hz range Intens

This document is not contractual - The SDMO company reserves the right to modify any of the characteristics stated in this document without notice, in a constant effort to improve the quality of its products.

SDMO Industries - 12bis, rue de la Villeneuve - CS 92848 - 29228 BREST CEDEX 2 - France - Tel +33(0)2 98 41 41 41 - Fax +33 (0)2 98 41 63 07 - www.sdmo.com

ACCESSORIES SUPPLIED



Funnel

User and maintenance manual

OPTIONS



R03 **Differential box R03**

This set includes a differential switch and a thermal circuit breaker.



R07 **Trolley kit R07**

Trolley kit for generating sets > 3 kW with a stretcher system for easy handling.



RH1 **Cover RH1**

#Housse de protection pour groupes électrogènes et motopompes SDMO



RPM **Set of male plugs RPM**

Male plugs for all models made up of : 2 x 16 A/230 V, EEC17: 1 x 16A/230 V, 1 x 32A/230 V and 1 x 16A/400V



RPQ **Earth spike RPQ**

For earthing your generator set. Galvanised 1 m long spike, supplied with 2 m of 10 mm² cable.