



DESCRIPTIVE

- Mechanic governor
- Mechanically welded chassis with antivibration suspension
- Main line circuit breaker
- Radiator for core temperature of 48/50°C max with mechanical fan
- Protective grille for fan and rotating parts (CE option)
- 9 dB(A) silencer supplied separately
- Charger DC starting battery with electrolyte
- 12 V charge alternator and starter
- Delivered with oil and coolant -30°C
- Manual for use and installation

POWER DEFINITION

PRP : Prime Power is available for an unlimited number of annual operating hours in variable load applications, in accordance with ISO 8528-1. ESP : The standby power rating is applicable for supplying emergency power in variable load applications in accordance with ISO 8528-1. Overload is not allowed.

TERMS OF USE

According to the standard, the nominal power assigned by the genset is given for 25°C Air Inlet Temperature, of a barometric pressure of 100 kPa (100 m A.S.L), and 30 % relative humidity. For particular conditions in your installation, refer to the derating table.

ASSOCIATED UNCERTAINTY

For the generating sets used indoor, where the acoustic pressure levels depends on the installation conditions, it is not possible to specify the ambient noise level in the exploitation and maintenance instructions . You will also find in our exploitation and maintenance instructions a warning concerning the air noise dangers and the need to implement appropriated preventive measures.

J110K

Engine ref.	4045HF120
Alternator ref.	AT00911T
Performance class	G3

GENERAL CHARACTERISTICS

Frequency (Hz)	50
Voltage (V)	400/230
Standard Control Panel	APM303
Optional control panel	TELYS
Optional Control Panel	Basic terminal block

POWER

Voltage	ESP		PRP		Standby Amps
	kWe	kVA	kWe	kVA	
200/115	88	110	80	100	318
240 TRI	88	110	80	100	265
230 TRI	88	110	80	100	276
220 TRI	88	110	80	100	289
220/127	79	99	72	90	260
415/240	88	110	80	100	153
400/230	88	110	80	100	159
380/220	88	110	80	100	167

DIMENSIONS COMPACT VERSION

Length (mm)	1950
Width (mm)	1084
Height (mm)	1330
Dry weight (kg)	1187
Tank capacity (L)	190

DIMENSIONS SOUNDPROOFED VERSION

Commercial reference of the enclosure	M129
Length (mm)	2554
Width (mm)	1150
Height (mm)	1680
Dry weight (kg)	1587
Tank capacity (L)	190
Acoustic pressure level @1m in dB(A)	78
Sound power level guaranteed (Lwa)	95
Acoustic pressure level @7m in dB(A)	66



J110K

ENGINE CHARACTERISTICS

GENERAL ENGINE DATA

Engine brand	JOHN DEERE
Engine ref.	4045HF120
Air inlet system	Turbo
Cylinders configuration	L
Number of cylinders	4
Displacement (L)	4.48
Charge Air coolant	Air/Air DC
Bore (mm) x Stroke (mm)	106 x 127
Compression ratio	17 : 1
Speed (RPM)	1500
Pistons speed (m/s)	6.35
Maximum stand-by power at rated RPM (kW)	100
Frequency regulation, steady state (%) +/- 2.5%	
BMEP (bar)	16.24
Governor type	Mechanical

COOLING SYSTEM

Radiator & Engine capacity (L)	20.20
Max water temperature (°C)	105
Outlet water temperature (°C)	93
Fan power (kW)	2.50
Fan air flow w/o restriction (m3/s)	3.70
Available restriction on air flow (mm H2O)	20
Type of coolant	Glycol-Ethylene
Thermostat modulating range HT (°C)	82-94

EMISSIONS

Emission PM (mg/Nm3) 5% O2	100
Emission CO (mg/Nm3) 5% O2	310
Emission HC+NOx (g/kWh)	
Emission HC (mg/Nm3) 5% O2	26

EXHAUST

Exhaust gas temperature @ ESP 50Hz (°C)	545
Exhaust gas flow @ ESP 50 Hz (L/s)	283
Max. exhaust back pressure (mm H2O)	750

FUEL

Consumption @ 110% load (L/h)	25.50
Consumption @ 100% load (L/h)	23.50
Consumption @ 75% load (L/h)	16.50
Consumption @ 50% load (L/h)	11.50
Maximum fuel pump flow (L/h)	108

OIL

Oil capacity (L)	13.50
Min. oil pressure (bar)	1
Max. oil pressure (bar)	5
Oil consumption 100% load (L/h)	0.0240
Oil sump capacity (L)	12.50

HEAT BALANCE

Heat rejection to exhaust (kW)	64
Radiated heat to ambient (kW)	10.50
Heat rejection to coolant (kW)	36

AIR INTAKE

Max. intake restriction (mm H2O)	625
Intake air flow (L/s)	106



J110K

ALTERNATOR CHARACTERISTICS

GENERAL DATA

Alternator ref.	AT00911T
Number of Phase	Three phase
Power factor (Cos Phi)	0.80
Altitude (m)	0 to 1000
Overspeed (rpm)	2250
Number of pole	4
Capacity for maintaining short circuit at 3 In for 10 s	No
Insulation class	H
T° class (H/125°), continuous 40°C	H / 125°K
T° class, standby 27°C	H / 163°K
AVR Regulation	Yes
Total Harmonic Distortion in no-load DHT (%)	<3
Total Harmonic Distortion, on load DHT (%)	<5
Wave form : NEMA=TIF	<50
Wave form : CEI=FHT	<2
Number of bearing	1
Coupling	Direct
Voltage regulation at established rating (+/- %)	0.50
Recovery time (Delta U = 20% transient) (ms)	500
Indication of protection	IP 23
Technology	Without collar or brush

OTHER DATA

Continuous Nominal Rating 40°C (kVA)	100
Standby Rating 27°C (kVA)	110
Efficiencies 100% of load (%)	92.10
Air flow (m3/s)	0.25
Short circuit ratio (Kcc)	0.5410
Direct axis synchro reactance unsaturated (Xd) (%)	287
Quadra axis synchro reactance unsaturated (Xq) (%)	172
Open circuit time constant (T'do) (ms)	2211
Direct axis transient reactance saturated (X'd) (%)	12.90
Short circuit transient time constant (T'd) (ms)	100
Direct axis subtransient reactance saturated (X''d) (%)	7.70
Subtransient time constant (T''d) (ms)	10
Quadra axis subtransient reactance saturated (X''q) (%)	16.10
Subtransient time constant (T''q) (ms)	10
Zero sequence reactance unsaturated (Xo) (%)	0.39
Negative sequence reactance saturated (X2) (%)	11.95
Armature time constant (Ta) (ms)	15
No load excitation current (io) (A)	0.71
Full load excitation current (ic) (A)	2.27
Full load excitation voltage (uc) (V)	28.50
Engine start (Delta U = 20% perm. or 50% trans.) (kVA)	267.07
Transient dip (4/4 load) - PF : 0,8 AR (%)	12
No load losses (W)	2316.52
Heat rejection (W)	6835.53
Unbalanced load acceptance ratio (%)	100

DIMENSIONS

Containment DW

Commercial reference of the enclosure	M129 DW
Length (mm)	2602
Width (mm)	1150
Height (mm)	1900
Dry weight (kg)	2006
Tank capacity (L)	505
Acoustic pressure level @1m in dB(A)	77
Sound power level guaranteed (Lwa)	95
Acoustic pressure level @7m in dB(A)	66

Containment DW 48H

Commercial reference of the enclosure	M129 DW48
Length (mm)	2602
Width (mm)	1150
Height (mm)	1948
Dry weight (kg)	2012
Tank capacity (L)	825
Acoustic pressure level @1m in dB(A)	77
Sound power level guaranteed (Lwa)	95
Acoustic pressure level @7m in dB(A)	66

APM303, comprehensive and simple



The APM303 is a versatile unit which can be operated in manual or automatic mode. It offers the following features:

- Measurements:
 - phase-to-neutral and phase-to-phase voltages, fuel level
 - (In option : active power currents, effective power, power factors, Kw/h energy meter, oil pressure and coolant temperature levels)
- Supervision:
 - Modbus RTU communication on RS485
- Reports:
 - (In option : 2 configurable reports)
- Safety features:
 - Overspeed, oil pressure, coolant temperatures, minimum and maximum voltage, minimum and maximum frequency
 - (Maximum active power P<66kVA)
- Traceability:
 - Stack of 12 stored events

For further information, please refer to the data sheet for the APM303.

TELYS, ergonomic and user-friendly



The highly versatile TELYS control unit is complex yet accessible, thanks to the particular attention paid to optimising its ergonomics and ease of use. With its large display screen, buttons and scroll wheel, it places the accent on simplicity and communication.

The TELYS offers the following functions:

Electrical measurements: voltmeter, frequency meter, ammeter.

Engine parameters: working hours counter, oil pressure, coolant temperature, fuel level, engine speed, battery voltage.

Alarms and faults: oil pressure, coolant temperature, failure to start, overspeed, alternator min./max., battery voltage min./max., emergency stop, fuel level.

Ergonomics: wheel for navigating around the various menus.

Communication: remote control and operation software, USB connections, PC connection.

For more information on the product and its options, please refer to the sales documentation.

Basic terminal block



The control unit can be used as a basic terminal block for connecting a control box.

Offers the following functions:

emergency stop button, customer connection terminal block, CE.