



XP-T9KM-AM-ALIZE

PORTABLE POWER

50Hz AM range Industrial

PRODUCT ADVANTAGES


- Mitsubishi 1500 tr/min long lasting professional engine
- Very large Autonomy
- Electric starter with batteries without maintenance
- complete control panel
- Low noise level

Zoom

A leading edge technology, designed for regular and intensive use, powerful and silent at the same time.

Divers

A leading edge technology, designed for regular and intensive use, powerful and silent at the same time.



XP-T9KM-AM-ALIZE

GENERAL SPECIFICATIONS

Range	Industrial
Frequency (Hz)	50
Max. power (LTP) (kW)	8.60
Max power. (LTP) (kVA)	10.75
Nominal voltage (V)	230
Number of phase	Single phase - 230V
Guaranteed acoustic power Lw(A)	86
Noise level dB(A) - 1m	70
Noise level dB(A) - 7m	57

ENGINE SPECIFICATIONS

Engine trademark	Mitsubishi
Engine type	S3L2 SD
Distribution	Fuel 1500
Start	Electrical
Fuel	Fuel
Autonomy (h)	20
Consumption (L/h]	2.50
Tank (L)	50
Oil Guard	Yes
Capacity (cm3)	1318
Oil capacity (L)	3.70

ALTERNATOR SPECIFICATIONS

Type	With collar and brush
Regulation	Electronic
Protection class	IP 21
Insulation class	H

PLUGS AND PANEL DESCRIPTIVE

2 120V 20A sockets (L5-20R GFCI) - circuit breaker + 1 240V 50A socket (HUK-4) - circuit breaker + differential protection+ MICS NEXYS(1)

DIMENSIONS AND WEIGHT

Lenght (cm)	175
Width (cm)	77.50
Height (cm)	123
Dry Weight (kgs)	544

PACKAGING

Packaging type	Canopy + Film
Length (cm)	175
Width (cm)	77.50
Height (cm)	123
Number of box by pallet	0
Pallet height (cm)	0

XP-T9KM-AM-ALIZE - PORTABLE POWER - 50Hz AM range Industrial

This document is not contractual - The SDMO company reserves the right to modify any of the characteristics stated in this document without notice, in a constant effort to improve the quality of its products.

SDMO Industries - 12bis, rue de la Villeneuve - CS 92848 - 29228 BREST CEDEX 2 - France - Tel +33(0)2 98 41 41 41 - Fax +33 (0)2 98 41 63 07 - www.sdmo.com

ACCESSORIES SUPPLIED



Funnel

User and maintenance manual

OPTIONS



CM308 **CM308 remote control** Remote control with separated case with start up/stop button, start up indicator and generating set defect - delivered without cable



VERSO-M **VERSO M automatic start panel** Automatic start up on lack of power (included engine preheating, battery charger, normal/back up reverser)



RMS **Puesta en servicio** Commissioning : compliance checks of the instalation, level controles, starting, no-load and load test, Instruction of the customer on the maintenance of the genset.



RBH1 **Cans of oil RBH1** Box of 24 o.5L cans of oil or 20 1 L cans of oil (SAE 15W40)



RBH0-5 **Cans of oil RBH0-5** Box of 24 0.5L cans of oil or 20 1 L cans of oil (SAE 15W40).



RPM **Set of male plugs RPM** Male plugs for all models made up of : 2 x 16 A/230 V, EEC17: 1 x 16A/230 V, 1 x 32A/230 V and 1 x 16A/400V



RPQ **Earth spike RPQ** For earthing your generator set. Galvanised 1 m long spike, supplied with 2 m of 10 mm² cable.